

MARMOFIX NATURA

Technical data

Description of the product

MARMOFIX DispersionsfarbeHD Weiss Innen: Emulsion paint of premium quality for interior use

- Great hiding power
- Superior whiteness
- Brilliant shades with long lasting color stability
- Smooth matt finish
- Great working and leveling properties without splashing
- Strong adhesion and quick drying
- Excellent resistance to frequent washing
- Ammonia free

Recommended uses

It is intended for protective and decorative use in interior wall surfaces of plaster, concrete, brick, wood, stucco, gypsum board, plastic (living rooms, offices etc). **MARMOFIX DispersionsfarbeHD Weiss Innen** is particularly suitable for painting fine rendered wall and ceiling surfaces, gypsum plasterboards, etc.

DIPSPERSIONSFARBE
HD weiss Innen



...GARANTIERTE
QUALITÄT!


Technical characteristics

Resin	Acrylic Copolymer
Density	1,60±0,05 gr/ml
Production viscosity (white) Storage viscosity (white)	105±5 KU 23°C 105±5 KU 23°C
Consumption	Depending on the absorbency, porosity, and the texture of the surface the average consumption for two coatings is: 0.20–0.25 kg/m ²
Dry through(white) Recoating time (white) Dry through (shades) Recoating time (shades)	40±10 Minuten 1½ Stunde 50±10 Minuten 2½ Stunde (Die Trocknungs- und Überarbeitungszeit kann sich bei niedrigen Temperaturen und hoher relativer Luftfeuchtigkeit verlängern.)
Shades	Available in white and in thousands of shades via the MARMOFIX TINTING SYSTEM (MTS)
VOC (Volatile Organic Compounds)	Limit value for this product Category A/a30g/l (2010). The product contains max. 29g/l.

Preparation of the substrate and Application instructions

Preparation of the substrate

The substrate must be clean, dry and free from all defective and poorly adhering material, dust, dirt, oils and salts. Old coatings that easily peel off should be removed.

New and porous surfaces should be impregnated with **TIEFGRUND TG-130 PRIMER**, diluted up to 50% with water.

Surfaces with mold and algae should be cleaned/disinfected before applying the primer.

Preparation and Application

Application method: Brush, roller, airless spray

Diluent: Water

Dilution: 10-20% v/v

MARMOFIX DispersionsfarbeHD Weiss Innen is usually applied in two coatings.

In continuous wall surfaces it should be applied without interruptions, in order to avoid unevenly painted surfaces, non-uniform drying etc.

The application must not be carried out at temperatures below +5°C and above +30°C. During and after all applications, the products must be protected from weather influences.

Clean the equipment with water immediately after use.

It is recommended that coated surfaces will not be washed until 25-30 days have elapsed from the application.

Handling and Storage

Keep out of reach of children. No special precautions are required when working with **MARMOFIX DispersionsfarbeHD Weiss Innen**. When the product is applied by spraying, use protective gloves, mask, and goggles. In case of contact with eyes or skin wash thoroughly with water, and if necessary seek medical attention.

Product residue should be disposed of in conformity with local regulations. It shouldn't be poured into sewers or the environment. Dry or hardened residue can be disposed of as construction site waste or domestic waste.

MARMOFIX DispersionsfarbeHD Weiss Innen must be stored in temperatures between +5 °C and +25 °C and away from sunlight. In unopened original buckets and under the above mentioned conditions, **MARMOFIX DispersionsfarbeHD Weiss Innen** can be stored for 24 months.

Packaging units

20 kg buckets

