

MARMOFIX NATURA

Technical data

Description of the product

MARMOFIX Voranstrich VA-150 Grund: Pigmented and filled with fine grained quartz sand, acrylic water based primer of premium quality for interior and exterior use

- Excellent undercoat for decorative plasters
- Increases the adhesion strength of plaster on smooth or non absorbent surfaces
- Combines deep penetration and the creation of a grained film on the surface
- Easy application and high spreading rate
- Great binding capacity and durability
- Strong adhesion and quick drying
- Uniform surface to the final coat

Recommended uses

MARMOFIX Voranstrich VA-150 Grund is ideal for ETICS and suitable for surfaces, such as plaster, concrete, old plaster, painted surfaces, bricks, wood etc. It is recommended for alkaline surfaces.

**VORANSTRICH
VA-150
GRUND**



...GARANTIERTE
QUALITÄT!


Technical characteristics

Resin	Special Acrylic Copolymer
Density	1,50±0,05 gr/ml
Production viscosity	15000-20000mPas, 23 °C
Storage viscosity	15000-20000mPas, 23 °C
Consumption	Depending on the absorbency, porosity, and the texture of the surface the average consumption for two coatings is: 0.25–0.30 kg/m ²
Dry through Recoating time	45±10 minutes 1±½ hours (Drying and recoating time may be prolonged under conditions of low temperature and high relative humidity)
VOC (Volatile Organic Compounds)	Limit value for this product Category A/g 30g/l (2010). The product contains max. 29g/l.

Preparation of the substrate and Application instructions

Preparation of the substrate

The substrate must be clean, dry and free from all defective and poorly adhering material, dust, dirt, oils and salts.

Old coatings that easily peel off should be removed.

Surfaces with mold and algae should be cleaned/disinfected before applying the primer.

Preparation and Application

Application method: Brush, roller

Diluent: Water

Dilution: Ready to use or max 10% v/v with water

MARMOFIX Voranstrich VA-150 Grund is applied in one coating.

The application must not be carried out at temperatures below +5°C and above +30°C. During and after all applications, the products must be protected from weather influences.

Clean the equipment with water immediately after use.

Handling and Storage

Keep out of reach of children. No special precautions are required when working with **MARMOFIX Voranstrich VA-150 Grund**. In case of contact with eyes or skin wash thoroughly with water, and if necessary seek medical attention.

Product residue should be disposed of in conformity with local regulations. It shouldn't be poured into sewers or the environment. Dry or hardened residue can be disposed of as construction site waste or domestic waste.

MARMOFIX Voranstrich VA-150 Grund must be stored in temperatures between +5 °C and +25 °C and away from sunlight. In unopened original buckets and under the above mentioned conditions, **MARMOFIX Voranstrich VA-150 Grund** can be stored for 24 months.

Packaging units

20 kg buckets

